







REV	REVISION RECORD	DATE	DRWN	CHKD	APVD
A	EC NO (RD-2019-179)	18DEC'19	JH	KH	CY



NOTES:

1. GENERAL TOLERANCE: ± 0.3 , $\pm 3^\circ$
2. REFERENCE MATING CONNECTOR IS KH1600063-20.
3. SEE THE FOLLOWING CHART FOR ACCEPTABLE TERMINAL AND WIRE
4. LIMIT THE HSG GATE BURR BELOW 0.3mm

UJU TERMINAL	KH1600059-21
WIRE INSULATION O.D	1.2 - 1.5mm (0.3, 0.35mm ²)

3	GREEN	SILICONE	KN0000012	020 4P BLOCK SEAL	1
2	GREEN	SILICONE	KN0000011	020 4F INNER SEAL	1
1	BLACK	PA66-GF30	KM1600062-20	020 SLD 4F HSG	1
NO	COLOR	MATERIAL	PART NO.	DESCRIPTION	Q'TY

A	REV
KH1600061-20	ASSEMBLY P/N

TOLERANCES UNLESS OTHERWISE SPECIFIED	UNIT MM
0 ±	THIRD ANGLE PROJECTION
0.0 ±	
0.00 ±	
0.000 ±	
0.0000 ±	
ANGLES ±	
PRODUCT SPEC	APPLICATION SPEC

DRWN JH RYU	 (주)우주일렉트로닉스 UJU Electronics co.,Ltd.			
CHKD KH PARK				
APVD CY CHOI	NAME 020(0.5mm) SEALED 4P FEMALE ASSEMBLY			
MATERIAL SEE TABLE				
FINISH/COLOR SEE TABLE				
WEIGHT	CUSTOMER DRAWING	DRAWING NO KH1600061		
	LOC	RESTRICTED TO	SIZE A3	SCALE 3:1
			SHEET 1 OF 1	REV A